



The First Operational Experiences with the New Load Frequency Control System Developed for SMM Control Block

Goran Jakupović, Nikola Obradović^,
Ninel Čukalevski*, Ismar Sinanović^*

**Mihajlo Pupin Institute, Serbia*

^EMS - Serbian Transmission System and Market Operator, Serbia

DEMSEE 2009

September 17-18, 2009


Belgrade, Serbia



SMM Control block

- Members:
 - Serbia (EMS)
 - Montenegro (EPCG)
 - FYR Macedonia (MEPSO)
- Established in 2007, as successor of JIEL control block

SMM block internal and external interconnections



Main responsibilities of SMM control block

- Coordination of secondary control (AGC) efforts
- Energy accounting
- Data exchange
- *In order to perform this tasks appropriate software has been developed*
 - SMM block LFC control software
 - Energy accounting software (EAS)

Control algorithm

- UCTE SMM block applies hierarchical control scheme
- Block coordinator calculates ACE's of block members and of whole SMM block
- Two operation modes are possible:
 - Pluralistic (normally used)
 - Hierarchical

Control algorithm cont'd

- In **pluralistic** mode ACE's of each block member are calculated "as usual" :

$$ACE_k = (P_k - P_{k0}) + B_{fk} (F - F_0)$$


- In **hierarchical** mode ACE's contain component proportional to whole block ACE

$$ACE_k = (P_k - P_{k0}) + B_{fk} (F - F_0) + h_k ACE_{SMM}$$

Software implementation

- Distributed application
 - *Control* (“real time”) *component* (**Linux C/C++ app**)
 - *Database* with configuration and dynamic data (schedules & real-time data) – (**MySQL 5.0.45**)
 - *User interface* (Microsoft Windows app’s based on **.NET Framework 2.0/3.5**)

Software implementation cont'd



Performance of SMM control block

- Criteria developed by UCTE ad-hoc group in 2004 ($ACE\sigma_{90}$ and $ACE\sigma_{99}$)
- Additional criterion used within SMM control block (Hourly average ACE within ± 20 MW margin)

$ACE_{\sigma_{90}}$ and $ACE_{\sigma_{99}}$ criterion's

- Indicators use hourly average values of ACE on monthly level
- $ACE_{\sigma_{90}}$ should not be exceeded more than 10% of time
- $ACE_{\sigma_{99}}$ should not be exceeded more than 1% of time

$ACE_{\sigma_{90}}$ and $ACE_{\sigma_{99}}$ criterion's

- Each control block should have his own value of σ_{90} and σ_{99} .

$$\sigma_{90} = 0,01645 \frac{20788 \sqrt{total_load_{control_block}}}{\sqrt{total_load_{UCTE}}}$$

$$\sigma_{99} = 0.02576 \frac{20788 \sqrt{total_load_{control_block}}}{\sqrt{total_load_{UCTE}}}$$

$ACE_{\sigma_{90}}$ and $ACE_{\sigma_{99}}$ criterion's

SMM Control block for the period April – June 2008

	calculated limits [MW]		Period of allowed excursions [% of time]		Period of excursions [% of time]	
	σ_{90}	σ_{99}	σ_{90}	σ_{99}	σ_{90}	σ_{99}
April 2008	48,39	75,77	10	1	30	19
May 2008	48,39	75,77	10	1	14	15
June 2008	48,39	75,77	10	1	21	4

$ACE_{\sigma_{90}}$ and $ACE_{\sigma_{99}}$ criterion's

- **SMM block was not able to fulfill criterion during observed period**
- **Reason:**
 - SMM block relies only on hydro power plants for secondary control.
 - Inflow was huge and capacity for control low
- **Solution:**
 - Serbian TSO (EMS) has started preparations (together with Serbian Power Utility - EPS) to introduce thermal units into secondary control

Performance criterion based on 20 MW error margin


- Control area must maintain its hourly average ACE within ± 20 MW margin or cross zero every 10 minutes during this hour
- This is most relaxed criterion used in SMM block

Performance criterion based on 20 MW error margin

NUMBER OF HOURS WITH FULFILLED CRITERION

	Number of hours with fulfilled criterion [%]		
	April 2008	May 2008	June 2008
Serbia	94	96	95
Montenegro	80	93	87
FYR Macedonia	63	83	69

Average hourly values of ACE (MWh/h) distribution on 20 MW intervals



Conclusions

- LFC System, developed for SMM Control block has proved his functionality, reliability and performance
- Current drawbacks are full dependence on hydro units, and still developing market environment.
- Additional improvement could be expected after the beginning of operation of thermal units in secondary control, and improvements in market mechanism

Thank you for attention

The First Operational Experiences with the New Load Frequency Control System Developed for SMM Control Block

Goran Jakupović, Nikola Obradović^,
Ninel Čukalevski*, Ismar Sinanović^*

**Mihajlo Pupin Institute, Serbia*

^EMS - Serbian Transmission System and Market Operator, Serbia

DEMSEE 2009

September 17-18, 2009

Belgrade, Serbia